



(43) International Publication Date  
4 November 2004 (04.11.2004)

PCT

(10) International Publication Number  
**WO 2004/093619 A1**

(51) International Patent Classification<sup>7</sup>: A47J 31/32

(21) International Application Number:  
PCT/EP2004/050556

(22) International Filing Date: 16 April 2004 (16.04.2004)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:  
PN2003A000028 23 April 2003 (23.04.2003) IT

(71) Applicant (for all designated States except US): WIT-  
TENBORG A/S [DK/DK]; Seebladsgade 1-3, DK-5000  
Odense C (DK).

(72) Inventors; and

(75) Inventors/Applicants (for US only): VAN HATTEM, Jan

Cornelis [NL/NL]; Utrechtsestraatweg 63, NL-3958 BN  
Amerongen (NL). DE REUS, Robert Francis [NL/NL];  
Schalmei 13, NL-6904 PZ Zavenaar (NL).


(74) Agent: GIUGNI, Valter; PROPRIA S.r.l., Via Mazzini,  
13, I-33170 Pordenone (IT).

(81) Designated States (unless otherwise indicated, for every  
kind of national protection available): AE, AG, AL, AM,  
AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,  
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,  
GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE,  
KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD,  
MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG,  
PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM,  
TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM,  
ZW.

(84) Designated States (unless otherwise indicated, for every  
kind of regional protection available): ARIPO (BW, GH,  
GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),

[Continued on next page]

(54) Title: BEVERAGE BREWING DEVICE



(57) Abstract: Beverage brewing device, in particular for brewing hot beverages such as coffee, tea, roasted-barley coffee, camomile tea and similar infusions, comprising substantially a brewing chamber (1), in which the substances needed to prepare the infusion are introduced through a mixing hopper (2), which is situated above said brewing chamber, and are mixed by compressed air being admitted therein as supplied by an air compression means (7), the device further comprising a removable filter (10) that closes the brewing chamber on the lower side thereof. The opening (5) connecting the mixing hopper (2) with the brewing chamber (1) is closed by an automatic valve (6), which is actuated by the compressed air supplied by said air compression means (7) via a delivery conduit (8). Very simple and rational technical solution.



Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

*For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*

**Published:**

— *with international search report*

5

10

**BEVERAGE BREWING DEVICE****DESCRIPTION**

The present invention refers to a brewing device for the preparation of  
15 beverages, in particular hot beverages such as coffee, tea, roasted-barley  
coffee, camomile tea and similar brews and infusions, which makes use of  
compressed air for filtering and mixing the substances that make up the  
beverage.

20 Brewing devices of the above-indicated kind are largely known in the  
art and substantially comprise a vertical cylindrical body, in which the  
substances in powder form and the water are introduced through a filling  
hopper, arranged above the cylinder, and are mixed-filtered by air being  
admitted under pressure thereinto. These devices enable beverages to be  
25 obtained, which are thoroughly homogenized and may be more or less  
flavoured or tasty, and possibly more or less frothy, according to the  
actual requirements of the buyers.

A brewing device of this kind is for example described in the Japanese  
30 patent publication JP-A-01-158592. The device disclosed in this Japanese  
patent provides for the possibility for compressed air to be let into the  
brewing cylinder through two different conduits, which debouch into the  
lower-side portion and the upper-side portion of the cylinder, respectively.

The two conduits are selectively opened by means of a three-way flow-diverting valve installed in the conduit that connects the air pump with the brewing cylinder.

5     The opening that establishes a communication between the filling hopper and the brewing cylinder is closable by a valve performing a reciprocating motion as driven by a specially provided motor. The solution described in this Japanese patent turns however out as being rather complicated from a structural point of view, as well as scarcely reliable  
10    from an functional point of view; it in fact calls for a number of different operating parts to be used, which imply quite high costs due to both the components and the assembly thereof.

It therefore is a main object of the present invention to provide a device  
15    for brewing beverages, which is particularly simple and rational in the operation and construction thereof owing to various functions being combined and integrated in view of reducing minimizing the number of moving parts of the device to a minimum, i.e. minimizing the number of those components which require being moved.

20    Within this general object, it is a purpose of the present invention to provide a beverage brewing device, which is capable of ensuring that the brewing chamber is duly flushed and washed during each operating cycle of the device.

25    Another purpose yet of the present invention is to provide a brewing device, whose component parts are provided so as to be easily and conveniently disassembled and removed to maintenance and cleaning purposes.

30    According to the present invention, these aims are reached in a brewing device incorporating the characteristics as recited in the appended claims.

Features and advantages of the present invention will anyway be more readily understood from the description that is given below by way of non-limiting example with reference to the accompanying drawing showing a schematical, partially cross-sectional view of the brewing device according to the present invention.

In the drawing, the brewing device is shown to substantially comprise a brewing chamber 1, in which the substances needed to prepare the infusion, i.e. the beverage are introduced through a filling and mixing hopper 2 that is situated above said brewing chamber. This hopper 2 is in turn supplied via a feeding mouth 3 that is connected with at least a reservoir (not shown), in which there is contained a substance, such as for instance ground coffee, which must be brewed.

The device itself can of course be provided with various reservoirs, each one of which contains a different substance for brewing. Preferably, all of these various reservoirs are directed with their delivery mouths towards the hopper 2. Furthermore, into the same hopper 2 there is conveyed, via a conduit 4, the hot water required to brew the selected substance.

To the hopper 2 there is separately associated a conduit 22 for venting air outside the device; this enables froth to be prevented from forming as the substances are mixed up in the same hopper.

The brewing chamber 1 and the hopper 2 are connected with each other via an opening 5.

According to the present invention, the opening 5 is closed by an automatic valve 6 that is actuated by means of a jet of compressed air.

This valve 6 is arranged with its axis extending vertically and is so shaped as to be able to be guided in such a manner as to displace reciprocatingly through the opening 5.

In a particular embodiment thereof, the valve 6 is in an umbrella-like shape and is provided on the upper surface thereof with a ring-shaped seal 11 adapted to close the opening 5 in a tight manner. The means provided to guide and retain the valve 6 in the opening 5 may be of any  
5 suitable type or kind known as such in the art; in the accompanying drawing, these means are simply represented by members shown to be coupled to each other in a loosely sliding manner.

The actuation of the valve 6 is brought about by means of a jet of  
10 compressed air, which is generated by an appropriate source 7, and which is delivered directly against the valve body. The compressed-air source 7 may be provided for example in the form of an axial reciprocating-piston compressor that is directly associated to the brewing chamber 1 (as shown in the Figure). Otherwise, use can be made here of a rotary compressor,  
15 which may be situated even far from the brewing chamber. In any case, the compressed air generated by the compressor 7 is delivered via a conduit 8 debouching below the valve 6, in such a manner as to cause it to act against the umbrella-shaped body of the same valve.

20 It will be readily appreciated that the shape of the valve 6 may be variously modified, provided that it keeps ensuring an automatic, tight closure of the opening 5 under the action of the compressed air.

In order to enable the liquid mixture that is produced in the hopper 2  
25 to flow out of the same hopper, the valve 6 is actuated into opening by the action of the negative pressure created within the brewing chamber 1 when the piston moves backwards after compression or, in the case of a different air-operated system, when it changes from compression mode into suction mode, exerting a corresponding action through the conduit 8.

30 Finally, the brewing device comprises a control valve 9, preferably of a ball type with retaining spring, or any other suitable type known as such in the art, for preventing the liquid from flowing or leaking out of the

brewing chamber prior to the compressed air being able to start exerting its action, as well as for enabling a negative pressure to build up during the return stroke of the piston or the suction phase of any other system that may be used. The valve 9 is associated to a filter 10, through which  
5 the brew is delivered and in which, upon the brew being in this way delivered therethrough, the retained residue is collected for removal.

The valve 9 is opened automatically by the pressure created by the piston in the brewing chamber, whereas it is closed by the action of the  
10 spring.

The brewing device according to the present invention works in the following manner.

15 To start with, the substances required for brewing (e.g. ground coffee and hot water) are delivered in an appropriately metered amount into the mixing hopper 2. The air compressor 7 is not operating; the valve 6 is open, whereas the valve 9 is closed. The metered water delivery is stopped with a certain delay in view of enabling the hopper 2 and the valve 6 to be  
20 flushed clean therewith. The mixture formed in the hopper flows down into the brewing chamber 1, where it dwells for a few seconds, i.e. the time required for the brewing to be completed.

Thereupon, the air compressor 7 is operated to generate a jet of  
25 compressed air that causes the valve 6 to close. The pressure within the brewing chamber 1 builds up, thereby causing the valve 9 to open and enabling in this way the brew to flow out by passing through the delivery filter.

30 While the air compressor 7 is holding the brewing chamber 1 under pressure and, therefore, the beverage is being dispensed, a small amount of water is let into the hopper 2, so that, when the air compressor changes from the compression mode into the suction mode, the valve 9 is biased

into closing by its own spring, whereas the valve 6 opens owing to the action of the negative pressure created in the meanwhile. At this point, the hot water contained in the hopper 2 flows down through the valve 6 which produces a kind of "umbrella" effect to urge the down-flowing water  
5 against the walls of the brewing chamber, thereby cleaning them from the brewing residues.

Then, the air compressor 7 is again operated to close the valve 6. In this manner, the valve 9 opens again and all residues are eliminated from  
10 the brewing chamber 1 and collected into the filter for removal.

Owing to them being largely known in the art, the description of other steps included in the operation of the brewing device, such as for instance the separation of the filter 10 from the brewing chamber 1 so as to enable  
15 the solid residues of the brew to be removed and the initial conditions for starting a new brewing cycle to be restored, is intentionally omitted. The whole operating cycle of the brewing device is controlled and managed by an appropriate automatic programme sequence control unit of a type known as such in the art.

20

It can be readily appreciated that the brewing device according to the present invention turns out as being particularly simple, reliable and efficient, thanks to the use of the automatic valve 6 that regulates all flows through the mixing hopper 2 and the brewing chamber 1 up to the filter  
25 10, from which the beverage is dispensed and the solid residue is removed. The number of the functional parts of the device is therefore reduced to a minimum and the related movements and displacements are extremely simplified.

30



### CLAIMS

1. Beverage brewing device, in particular for brewing hot beverages such as coffee, tea, roasted-barley coffee, camomile tea and similar  
5 infusions, comprising substantially a brewing chamber (1), in which the substances needed to prepare the infusion are introduced through a mixing hopper (2), which is situated above said brewing chamber, and are mixed by compressed air being admitted therein as supplied by an air compression means (7), the device further comprising a removable filter  
10 (10) that closes the brewing chamber on the lower side thereof, **characterized in that** the opening (5) connecting the mixing hopper (2) with the brewing chamber (1) is closed by an automatic valve (6), which is actuated by the compressed air supplied by said air compression means (7) via a delivery conduit (8).

15

2. Beverage brewing device according to claim 1, **characterized in that** the automatic valve (6) is in an umbrella-like shape so as to be able to diffuse the water against the walls of the brewing chamber, thereby enabling them to be flushed clean.

20

3. Beverage brewing device according to claim 1 or 2, **characterized in that** the delivery conduit (8) of the compressed air extends into the brewing chamber (1) to debouch below said automatic valve (6).


25 4. Beverage brewing device according to any of the preceding claims or combination thereof, **characterized in that** said automatic valve (6) is arranged with its axis extending vertically and is so shaped and provided with sealing means (11) as to be able to tightly close the opening (5) when compressed air is being delivered.

30

5. Beverage brewing device according to any of the preceding claims or combination thereof, **characterized in that** above said valve (6), and

associated to the hopper (2), however separated therefrom, there is provided an air venting conduit (22).

6. Beverage brewing device characterized by what has been described  
5 and illustrated in and with reference to the accompanying drawings.



# INTERNATIONAL SEARCH REPORT

International Application No

PCT/EP2004/050556

**A. CLASSIFICATION OF SUBJECT MATTER**  
IPC 7 A47J31/32

According to International Patent Classification (IPC) or to both national classification and IPC

**B. FIELDS SEARCHED**

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 A47J

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal, WPI Data, PAJ

**C. DOCUMENTS CONSIDERED TO BE RELEVANT**

| Category * | Citation of document, with indication, where appropriate, of the relevant passages       | Relevant to claim No. |
|------------|--|-----------------------|
| X          | US 3 478 670 A (FUQUA NORMAN L)<br>18 November 1969 (1969-11-18)<br>figures 1,34         | 1-5                   |
| A          | US 3 440 952 A (MEROLA CARL R ET AL)<br>29 April 1969 (1969-04-29)<br>the whole document | 1-5                   |

☐ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

**\* Special categories of cited documents :**

\*A' document defining the general state of the art which is not considered to be of particular relevance

\*E' earlier document but published on or after the international filing date

\*L' document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

\*O' document referring to an oral disclosure, use, exhibition or other means

\*P' document published prior to the international filing date but later than the priority date claimed

\*T' later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

\*X' document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

\*Y' document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

\*G' document member of the same patent family

Date of the actual completion of the international search

22 July 2004

Date of mailing of the international search report

28/07/2004

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2  
NL - 2280 HV Rijswijk  
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,  
Fax: (+31-70) 340-3016

Authorized officer

Fritsch, K

# INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/EP2004/050556

| Patent document<br>cited in search report |   | Publication<br>date | Patent family<br>member(s)                                     | Publication<br>date                                  |
|---|---|---------------------|--|--|
| US 3478670                                | A | 18-11-1969          | CH 509067 A<br>DE 1932805 A1<br>FR 2014423 A5<br>JP 49009668 B | 30-06-1971<br>02-01-1970<br>17-04-1970<br>06-03-1974 |
| US 3440952                                | A | 29-04-1969          | NONE   |  |